



## AG-IPDV2-30 1080P IP Dome Camera

### Key Feature:


1080P

1. HD Megapixel with P2P&ONVIF
2. 2.8mm~12mm vari focal lens
3. 30m IR,36pcs Leds
4. Support multi-users remote viewing via PC CMS software, Web browser, 3g Mobile phone
5. HTTP,TCP/IP,UDP,FTP,SMTP,PPPoE,DDNS,DNS,DHCP,NTP,RTSP,UPNP,etc
- 6.IP66 Waterproof
- 7.CE/FCC/Rohs
8. POE optional

### Specification:

Model	AG-IPDV2-30
Sensor	1/2.7 1080P CMOS sensor,HI3516CV300
Resolution	1920*1080@30fps
Compression	H.265/H.264 Main Profile/Baseline
Stream flow	Support dual stream
Bit Rate	128-8192kbps
Bit Rate Type	CBR/VBR
S/N Ratio	>50DB
Electronic shutter	1/5-1/15,000 /S
Image enhancement	Auto White Balance,Backlight compensation,Brightness,Contrast,Saturation adjusted
Subtitles input	Support channel name, date/time
IR Filter	IR-CUT
IR-led	36pcs 5mm leds
IR distance	30M
Electronic shutter	1/5-1/15,000 /S
lens	2.8~12mm vari focal Lens (3Mega pixel lens)
Audio	N/A
Protocol	HTTP, TCP/IP, UDP, SMTP, DDNS, DNS, SNTP, DHCP, FTP, RTP, RTSP, UPNP, ONVIF, 28181
Ethernet	Ethernet (10/100 Base-T),RJ-45 connector
Safety	IP address filtering,User level password protection, The user access log
WEB Browser	Microsoft Internet Explorer 6.0 and above,Google,Firefox etc.
Mobile Phone	Support iPhone,Android,Bit rate:32K – 512K adjustable,Frame rate:6–12 fps
Software Management	CMS and the devices Compatible with ONVIF
Event action	Files are stored to the back end equipment,Send E-mail,Send SMS,Zoom in alarm,Pop ap map,Go to PTZ preset pos etc
Remote Access	DDNS, Software, P2P
Accessories	Power adapter, Network cable, Stand, Operation manual, CD, Screw bag
Temperature	-20°~60°C
Humidity	-10~85%
Power Consumption	DC 12V ,Module power consumption is less than 2 W

The specification is subject to change without notice.

+593 (4) 256-8289 

<https://aglar.com.ec/> 